LGMG

A14JE

ARTICULATING BOOM LIFT

- Battery powered provides quiet, zero-emission and long battery duty cycle.
- Proportional control ensures smooth driving, precise positioning and comfortable operation.
- Self-leveling platform together with hydraulic platform rotation delivers exceptional productivity.
- Intelligent self-diagnostic system for quick troubleshooting.
- Lead-acid battery, lithium battery（A14JE-Li) two options.

HONOR US EQUIPMENT (HK) LIMITED
譽豪設備(香港)有限公司

LGMG Electric - Articulating Boom Lift

SPECIFICATIONS

MODELS	A14JE (A45JE)	
Measurements	Metric	Imperial
Work Height Max.	15.8m	51'10"
Platform Height Max.	13.8m	45'3"
Horizontal Outreach	7.81m	25'7"
Up and Over Height	7.26m	23'10"
Platform Length	1.83m	6'
Platform Width	0.76m	2'6"
Ⓐ Stowed Length	6.66m	21'10"
Length-Transport (jib tucked)	5.85m	19'2"
Ⓑ Stowed Width	1.8m	5'11"
Ⓒ Stowed Height	1.98m	6'6"
Height-Transport	2.6m	8'6"
Ⓓ Wheelbase	2.03m	6'8"
Ⓔ Ground Clearance	0.24m	9"
PRODUCTIVITY		
Max. Platform Occupancy	2	
Platform Capacity	230kg	510 lbs
Turning Radius-Inside	1.83m	6'
Turning Radius-Outside	4.1m	13'5"
Turntable Rotation	355°	355°
Max.Slope	3°/3°	3°/3°
Max. Drive Speed (Stowed)	4.8km/h	3mph
Max. Drive Speed (Raised)	1km/h	0.62mph
Gradeability	30%	30%
Tire Type	Foam-filled non-marking	
Tire Models	9-14.5	
Ground Pressure, Tyres	820.8 kPa	119 psi
POWER		
Lead-acid Battery	48V(8x6V),390Ah,FLA	
Lithium Battery (A14JE-Li)	48V 280Ah	
HYDRAULIC SYSTEM		
Hydraulic Oil Capacity	30L	7.9gal
WEIGHT		
Machine Weight	7,500kg	16,535 lbs

STANDARD FEATURES	
Proportional control	Platform auto-leveling system
Horn/Hour meter	On-board diagnostic system
Tilt alarm with lift cut-out	Rear-wheel drive and break
Emergency stop button	Over tilt protection system
Anti-collision protection	Overload sensing system
Full-height drive	Descent alarm with flashing beacon
Telematics connector	Foam-filled non-marking tires
Platform tool box	AC power to platform

OPTIONAL	
Telematics	Solid tires
Biodegradable hydraulic oil	Solid non-marking tires





A14JE Working Range



Please contact LGMG or a local dealer for more details.
LGMG reserves the right to change technical data without prior notice. All photos and pictures in this brochure are for promotional purposes only.

HONOR US EQUIPMENT (HK) LIMITED 譽豪設備(香港)有限公司

LINGONG HEAVY MACHINERY CO., LTD.
Address: No. 2676, Kejia Road, Jinan, Shandong, China
Email: sales@lgmg.com.cn Tel: +86 531 6787 9283

LGMG Europe B.V.
Address: Donker Duyvisweg 301, 3316 BL Dordrecht, The Netherlands
Email: sales@lgmgeurope.com Tel: +31 850 642 777

LGMG North America Inc.
Address: 4105 Live Oak Drive, Suite 100, The Colony, Texas 75056 United States
Email: sales@lgmgna.com Tel: +1 833 288 5464

www.lgmglifts.com

LGMG
RELIABILITY IN ACTION